

TRANSFER SETTINGS

MiniMed™ 780G Replacement Pump

Transfer Settings for the MiniMed 780G Replacement Pump

STEP 1 – Before you send your original pump back, copy your current settings onto the insulin pump settings form. If for any reason you cannot copy the settings, please contact your healthcare professional or refer to your CareLink™ Personal reports.

STEP 2 – Insert a AA battery into your new pump. You can use either a lithium, alkaline or rechargeable battery.

STEP 3 – Follow the instructions found in this guide to enter the settings that you have recorded on the insulin pump settings form into your new pump. For additional information on your pump, please consult the MiniMed pump system user guide.

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Settings Form for the MiniMed 780G insulin pump

We recommend that you record all settings on this form and use this form as reference when you enter your settings into the new pump

Delivery Settings, Device Settings, SmartGuard

DELIVERY SETTINGS	DELIVERY SETTINGS (CONT.)
BOLUS WIZARD SETUP:	PRESET BOLUS SETUP:
Menu > ∅ > Delivery Settings > Bolus Wizard Setup	Menu > ♥ > Delivery Settings > Preset Bolus Setup
Bolus Wizard: ☐ On ☐ Off	Preset Bolus Name:
Carb Ratio:	Bolus: U Type:
12:00 A g/U	Now Square
g/U	Duration hr
g/U	BOLUS INCREMENT:
Insulin Sensitivity Factor:	Menu > ∅ > Delivery Settings > Bolus Increment
12:00 A mg/dL/U	□ 0.025 U □ 0.05 U □ 0.1 U
mg/dL/U	MAX BASAL/BOLUS:
mg/dL/U	Menu > ♥ > Delivery Settings > Max Basal/Bolus
BG Target:	Max Basal: U/hr Max Bolus: U
12:00 Å mg/dL	BOLUS SPEED:
	Menu > ♥ > Delivery Settings > Bolus Speed
	☐ Standard ☐ Quick
Active Insulin Time: hr	EASY BOLUS:
BASAL PATTERN SETUP:	Menu > ∅ > Device Settings > Easy Bolus
Menu > ∅ > Delivery Settings > Basal Pattern Setup	☐ On ☐ Off Step Size U
Basal 1:	AUTO SUSPEND:
12:00 A U/hr	Menu > ♥ > Device Settings > Auto Suspend
U/hr	Alarm: □ On □ Off
U/hr	Time: hr
Basal Pattern Name:	DEVICE SETTINGS
12:00 A U/hr	SENSOR:
U/hr	Menu > ♥ > Device Settings > Sensor
U/hr	□ On □ Off
PRESET TEMP SETUP:	DISPLAY:
Menu > ∅ > Delivery Settings > Preset Temp Setup	Menu > ∅ > Device Settings > Display Options
Preset Temp Name:	Brightness \ \Bar\ Auto
Type: Rate U/hr Percent %	Backlight sec / min
Duration hr	SMARTGUARD
DUAL/SOUARE WAVE:	Menu > ○
Menu > ② > Delivery Settings > Dual/Square Wave	SmartGuard: □ On □ Off
Dual: □ On □ Off	SMARTGUARD SETTINGS:
Square: On Off	Menu > > SmartGuard Settings
	Target: mg/dL
	Auto Correction: On Off
	aco concedion. — on — on

Alert Settings

HIGH ALERT Menu > ∅ > Alert Settings > High Alert					
High Limit	Alert before high	Time before high	Alert on high	Rise Alert	Rise Limit ^a
12:00A mg/dL	□On	min	□On	□On	Custom mg/dL/min or $\uparrow \mid \uparrow \uparrow \uparrow \uparrow \uparrow$
mg/dL	□On	min	□On	□On	Custom mg/dL/min or $\uparrow \mid \uparrow \uparrow \uparrow \uparrow \uparrow$
mg/dL	□On	min	□On	□On	Custom mg/dL/min or $\uparrow \mid \uparrow \uparrow \uparrow \uparrow \uparrow$
SNOOZE Menu > @ > Alert Settings > Snooze High & Low > High Snooze: hr					

^a Option only available when the Rise Alert feature is set to on

LOW ALERT Menu > ③ > Alert Settings > Low Alert					
Low Limit	Alert before low	Alert on low	Suspend before low	Suspend on low	Resume basal alerta
12:00A mg/dL	□On	□On	□On	□On	□On
mg/dL	□On	□On	□On	□On	□On
mg/dL	□On	□On	□On	□On	□On
SNOOZE Menu > ③ > Alert Settings > Snooze High & Low > Low Snooze: hr					

^a Option only available when the Suspend on low feature or the Suspend before low feature is set to on

Programming the MiniMed 780G insulin pump

Startup Wizard

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Once you've inserted the battery, the pump powers up and the Startup Wizard begins; it will guide you through setting language, time format, and current time and date.

- 1. Select English.
- 2. When the **Select Time Format** screen appears, select a **12 Hour** or a **24 Hour** time format.
- When the Enter Time screen appears, the hour will be flashing. Press ∧ or ∨
 to the correct hour and press ○.
- The AM / PM will be flashing. Press or if needed and press O. Select Next.
- When the Enter Date screen appears, select Year. Press ∧ or ∨ to the correct year and press ○. Repeat this step to set up Month and Day. Select Next.
- The Rewinding screen will briefly appear, followed by a confirmation message.
 Select OK










Setting Max Basal

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Menu > ∅ > Delivery Settings

- 1. Select Max Basal/Bolus and press O.
- 2. Select Max Basal. A confirmation message appears. Select Continue.
- Select Max Basal to enter the U/hr amount. Use and to set the Max Basal amount. Press ○.
- 4. Select Save.





Setting Max Bolus

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Menu > ♥ > Delivery Settings

- 1. Select Max Basal/Bolus and press O.
- 2. Select Max Bolus. A confirmation message appears. Select Continue.
- Select Max Bolus to enter the units (U) amount. Use and to set the Max Bolus amount. Press ○.
- 4. Select Save.

Delivery Settings
Bolus Wizard Setup
Basal Pattern Setup
Max Basal/Bolus
Dual/Square Wave
Bolus Increment

Max Basal/Bolus				
Max Basal	2.00 U/hr			
Max Bolus	10.0 ∪			

Setting a Basal Pattern

WARNING: The pump is intended to be used with a basal pattern. The basal pattern must be manually entered and saved into the pump. The pump will operate with a basal rate of 0.0 U/hr until a basal pattern is entered and saved. There is no reminder message to program basal rates. Consult a healthcare professional to determine what basal pattern is needed. For more information about basal patterns, consult the MiniMed 780G System User Guide.

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Menu > ∅ > Delivery Settings > Basal Pattern Setup


- 1. Select Basal 1.
- 2. Select **Options**, then select **Edit**.
- Press to enter End time. Press to leave the end time at 12:00A. If you are setting multiple rates use ∧ or ∨ to change the end time and press ○.
- 4. Press ∧ to enter **U/hr** and press ○.
- 5. Continue adding end times and basal rates as needed. The end time for your last rate must be **12:00A**.
- The Review option appears only when the last end time in your basal pattern is set to 12:00A. Select Review after all rates are entered to go to the next screen.

Note: Your basal rates have not yet been saved.

A screen appears that lets you review your basal pattern. Press
 to review
all the settings. If you need to make any changes, press to return to the edit
screen.

Note: If you press to return to the edit screen without saving, your changes will not be saved. After making any changes on the edit screen, select **Review** to return to the review screen.

8. Select Save. If you do not select Save, your changes are not saved.



CAUTION: If you have not selected Save after settings are entered and the screen goes dark, the entered settings will not be saved.

Turn On and Set Up the Bolus Wizard Feature

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Menu > ♥ > Delivery Settings > Bolus Wizard Setup

- 1. Select Bolus Wizard to turn the feature on.
- 2. Press \vee to see the rest of the message then select **Next**.
- 3. Review the description of carb ratio and select Next.
- Press to enter End time. Press again to leave the end time at 12:00A. If you are setting multiple carb ratios use ∧ or ∨ to change the end time, then press ○.
- Press ∧ or ∨ to enter g/U then press ○. Continue adding end times and carb ratios as needed.
- 6. Select Next when done.
- 7. Review the description of insulin sensitivity factor and select **Next**.
- Press to enter End time. Press again to leave the end time at 12:00A. If
 you are setting multiple insulin sensitivity factors, use ∧ or ∨ to change the
 end time, then press ○.
- 10. Select Next when done.
- 11. Review the description of BG target and select Next.
- Press to enter End time. Press again to leave the end time at 12:00A. If you are setting multiple BG targets, use or to change the end time, then press ○.
- 13. Press \wedge or \vee to enter the low limit (Lo) and then press \circ .
- 14. Press o v v to enter the high limit (Hi) and then press O. Continue adding end times and BG targets as needed.
- 15. Select Next when done.
- 16. Review the description of active insulin time and select **Next**.
- 17. Press O to enter the duration for the active insulin time.
- 18. Press \wedge or \vee to enter the hours of duration then press \circ .
- 19. Select Save.

The Bolus Wizard feature setup is now complete.





Turn Sensor On

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Menu > [⊕] > Device Settings

 Select Sensor to turn the feature on. You can now access the SmartGuard menu and enter the SmartGuard settings.





Pair the Transmitter

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.


Menu > €

- Attach Guardian™ 4 transmitter to the charger and place the transmitter (attached to the charger) next to the pump.
- Select Pair New Device on the pump and immediately remove the transmitter from the charger.
- The Select Device screen appears with a list of available devices. Select the CGM device that matches the serial number indicated on the back of the transmitter.

Your pump displays a message if the pump and transmitter are paired successfully. When the transmitter is communicating with the pump, the Sensor feature is turned on and $\widehat{\nabla}$ appears on the Home screen.







Programming High SG Settings

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.


Menu > ∅ > Alert Settings

- 1. Select **High Alert**. The **High Setup** screen appears.
- Press on the time segment. Press again to leave the End time at 12:00A.
 If setting multiple time segments, press ^ to enter the end time of the first segment, and press ○.
- 3. Press \wedge or \vee to set the high limit (Hi) and press \circ . Press \circ to continue.
- 4. Select each setting you wish to turn on. If a setting is on, select it again to turn it off.
- Once settings are selected, select Next. If needed, continue adding time segments and settings to complete the 24-hour period. When done, select Review.
- 6. Verify that settings are correct and select Save.

Your High Setup is now complete.









Programming Low SG Settings

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Menu > ⋄ > Alert Settings

- 1. Select Low Alert. The Low Setup screen appears.
- Press on the time segment. Press again to leave the End time at 12:00A.
 If setting multiple time segments, press ^ to enter the end time of the first segment, and press ○.
- 3. Press ∧ or ∨ to set the low limit (Lo) and press ○. Press to continue.
- 4. Select each setting you wish to turn on. If a setting is on, select it again to turn it off.
- Once settings are selected, select Next. If needed, continue adding time segments and settings to complete the 24-hour period. When done, select Review.
- 6. Verify that settings are correct and select Save.

Your Low Setup is now complete.





Low Setup

End

8:00 A

On

On

60 mg/dL

Start

12:00 A



Turn SmartGuard On

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Menu > ♡

- 1. Select **SmartGuard** to turn the SmartGuard feature on.
- 2. Review the message on the screen and select **OK**.





Note: The SmartGuard warm-up period begins at the first midnight after the pump starts delivering insulin. If you turn SmartGuard on before the warm up is complete, you may receive an alert at midnight to enter a BG for SmartGuard. You may want to wait until day 3 of your pump use to avoid this alert at midnight.

Programming SmartGuard Settings

Note: The settings shown in this guide are for illustration purposes only — your settings may be different.

Note: Make sure you consult with your healthcare provider on your personalized settings before programming the SmartGuard settings.

Menu > ○ > SmartGuard Settings

- 1. Review the Target.
- 2. Press O to change the target.
- 3. Press \wedge or \vee to the desired target and then press \circ .
- 4. Check to make sure that **Auto Correction** is set to **On**. Select **Save**.







Note: Please take some time to review ALL your settings and ensure they have been correctly saved.

Technical Support

In Need of Technical Assistance?

24-Hour Technical Support is here to help Call 1.800.646.4633

For medical advice, contact your healthcare team.

Medtronic



Medtronic MiniMed

18000 Devonshire Street Northridge, CA 91325 USA 1 800 646 4633 +1 818 576 5555 www.medtronicdiabetes.com

RF: M994838A001

© 2023 Medtronic M037938C001_1 2023-05-10



M037938C001